

**LISTING OF CLAIMS**

1. (original) An emission treatment system for treatment of an exhaust stream comprising NOx and particulate matter, the emission treatment system comprising:

- a) an oxidation catalyst;
- b) an injector in fluid communication with and downstream of the oxidation catalyst, wherein the injector periodically meters ammonia or an ammonia precursor into the exhaust stream; and
- c) a wall flow monolith in fluid communication with and downstream of the injector, wherein the wall flow monolith has a plurality of longitudinally extending passages formed by longitudinally extending walls bounding and defining said passages, wherein the passages comprise inlet passages having an open inlet end and a closed outlet end, and outlet passages having a closed inlet end and an open outlet end,

wherein the wall flow monolith comprises an SCR catalyst composition that permeates the walls at a concentration of at least  $1.3 \text{ g/in}^3$ ; wherein the wall flow monolith has a wall porosity of at least 50% with an average pore size of at least 5 microns.

2. (original) The emission treatment system of claim 1, wherein the SCR catalyst composition that permeates the walls of the wall flow monolith so that the walls have a wall porosity of from 50 to 75% with an average pore size of from 5 to 30 microns.

3. (original) The emission treatment system of claim 1, wherein the SCR catalyst composition comprises a zeolite and base metal component selected from one or more of a copper and iron component.

4. (original) The emission treatment system of claim 3, wherein the base metal component is a copper component.

5. (original) The emission treatment system of claim 4, wherein the zeolite of the SCR catalyst composition has a silica to alumina ratio of at least about 10.

6. (original) The emission treatment system of claim 5, wherein the zeolite of the SCR catalyst composition is a beta zeolite.

7. (original) The emission treatment system of claim 1, wherein there is from  $1.6$  to  $2.4 \text{ g/in}^3$  of SCR catalyst composition disposed on the wall flow monolith.

8. (original) The emission treatment system of claim 1, wherein the oxidation catalyst comprises a platinum group metal component.

9. (original) The emission treatment system of claim 8, wherein the oxidation catalyst further comprises a zeolite component.

10. (original) The emission treatment system of claim 1, further comprising a diesel engine upstream of, and in fluid communication with the oxidation catalyst.

11. (original) The emission treatment system of claim 1, wherein the oxidation catalyst is disposed on a honeycomb flow through monolith substrate or an open cell foam substrate.

12-24. (cancelled)

Respectfully submitted,

Dated: June 27, 2006

By: /Scott S. Servilla/

Scott S. Servilla  
Reg. No. 40,806  
Telephone (732) 815-0404

Chief Patent Counsel  
Engelhard Corporation  
101 Wood Avenue  
P.O. Box 770  
Iselin, NJ 08830-0770